

FORM PTO-1390

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

**TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371**

50212-225

U.S. APPLIC. NO. (if known, see 37 CFR 1.5)

09/830631

INTERNATIONAL APPLICATION NO.

INTERNATIONAL FILING DATE

PRIORITY DATE CLAIMED

PCT/JP99/06038

October 29, 1999

October 30, 1998

TITLE OF INVENTION

ION IMPLANTATION APPARATUS

APPLICANT(S) FOR DO/EO/US

Hiroyuki ITO and Hiroshi ASECHI

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information.

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made, however, the time limit for making such amendment has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☒ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification
15. ☐ A change of power of attorney and/or address letter
16. ☒ Other items or information.

International Search Report prepared by JPO
Forms PCT/IB/304 and PCT/IB/308
Front page of published International application
Associate Power of Attorney

U.S. APPLIC. NO. (if known, see 37 CFR 1.50) <div style="font-size: 24pt; font-weight: bold;">09/830631</div>		INTERNATIONAL APPLICATION NO. PCT/JP99/06038		ATTORNEY'S DOCKET NUMBER 50212-225	
--	--	---	--	---------------------------------------	--

				CALCULATIONS	PTO USE ONLY
17. <input checked="" type="checkbox"/> The following fees are submitted: <div style="display: flex; justify-content: space-between;"> <div> Basic National Fee (37 CFR 1.492(a)(1)-(5)): Search Report has been prepared by the EPO or JPO International preliminary examination fee paid to USPTO (37 CFR 1.482) No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) </div> <div style="text-align: right;"> \$860.00 \$690.00 \$710.00 \$1,000.00 \$100.00 </div> </div> <div style="text-align: right; margin-top: 10px;"> ENTER APPROPRIATE BASIC FEE AMOUNT = </div>					
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e))				\$	
Claims	Number Filed	Number Extra	Rate		
Total Claims	6 -20 =	0	x \$18.00	\$	
Independent Claims	1 -3 =	0	x \$80.00	\$	
Multiple dependent claim(s) (if applicable)			+ \$270.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$ 860.00	
Reduction by 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).				\$	
SUBTOTAL =				\$ 860.00	
Processing fee of \$130.00 for furnishing the English translation later than the <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f))				\$	
TOTAL NATIONAL FEE =				\$ 860.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				\$ 40.00	
TOTAL FEES ENCLOSED =				\$ 900.00	
				Amount to be: refunded	\$
				charged	\$

a. ☐ A check in the amount of \$ _____ to cover the above fees is enclosed

b. ☒ Please charge my Deposit Account No. 500417 in the amount of \$ 900.00 to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 500417. A duplicate copy of this sheet is enclosed

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

McDERMOTT, WILL & EMERY
 600 13th Street, N.W.
 Washington, DC 20005-3096
 (202) 756-8000
 Facsimile (202) 756-8087

SIGNATURE

Arthur J. Steiner

NAME

26,106

REGISTRATION NUMBER

April 30, 2001

DATE

VERIFICATION

The undersigned, of the below address, hereby certifies that he/she well knows both the English and Japanese languages, and that the attached is an accurate English translation of the PCT application filed on October 29, 1999 under

No. PCT/JP99/06038.

The undersigned declares further that all statements made herein of his/her own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Signed this 26th day of April, 2001.

Signature:


Name: Shiro TERASAKI

Address: c/o Soei Patent and Law Firm
Okura-Honkan, 6-12, Ginza 2-chome, Chuo-ku,
Tokyo 104-0061 Japan

5/PRTS

09/830631
JC18 Rec'd PCT/PTO 30 APR 2001
TMW99-31

DESCRIPTION

ION IMPLANTATION APPARATUS

Technical Field

5 The present invention relates to ion implantation apparatus and, more particularly, to ion implantation apparatus that can prevent a substrate from being contaminated by contaminant particles from a charged particle generator.

10 Background Art

 Large-current ion implantation apparatus performs ion implantation with an ion beam having a large current value in order to introduce a number of ions per unit time into a substrate. For this reason, the substrate itself is gradually charged up during execution of the ion implantation. If this charge build-up results in discharge, the substrate can be damaged by the discharge. In order to avoid such an accident, a charge neutralizer is used to prevent the charge build-up on the substrate. The charge neutralizer generates electrons for relieving the damage due to the charge of the substrate, whereby the negative charge of the electrons neutralizes the positive charge of ions to be implanted.

25 Disclosure of the Invention

 However, the charge neutralizer is constructed to

heat a filament by supplying an electric current thereto in order to generate the electrons, and thus not only the electrons but also metal particles making the filament jump out of the heated filament. If such metal particles reach the substrate, they will cause an unwanted effect on devices to be formed on the substrate in many cases. For this reason, the charge neutralizer becomes one of contamination sources for the substrate.

10 An object of the present invention is to provide an ion implantation apparatus that can reduce such metal contamination.

15 An ion implantation apparatus according to the present invention comprises an ion source section for generating ions; an ion implantation section for implanting the ions generated in the ion source section, in a substrate; a charged particle generator for generating charged particles having an opposite charge to that of the ions; a beam guide section having an inlet aperture for accepting the ions from the ion source section, an outlet aperture for delivering the ions to the ion implantation section, a guide tube extending from the inlet aperture to the outlet aperture, and an introducing section having an opening thereof in an internal surface of the guide tube, for introducing the charged particles from the charged

20

25

particle generator into the guide tube; and a shield section located between the opening of the introducing section and the outlet aperture inside the guide tube.

5 In this structure, the beam guide section for the ions generated in the ion source section to pass toward the ion implantation section is provided with the charged particle generator for generating the charged particles having the opposite charge to that of the ions. Therefore, this charged particle generator also
10 generates contaminant particles of contaminating matter for the substrate. However, since the shield section located between the opening of the introducing section and the outlet aperture is provided inside the guide tube, it can block paths of flight of contaminant
15 particles jumping out through the opening of the internal wall of the guide tube and reaching the substrate.

In the ion implantation apparatus according to the present invention, the shield section may have a
20 shield surface intersecting with straight lines running from points on a surface specified by the opening of the introducing section to points on a surface of the substrate to be implanted, placed in the ion implantation section.

25 With provision of this shield surface, it blocks paths of contaminant particles jumping out through the

opening of the internal wall of the guide tube and directly arriving at the substrate.

In the ion implantation apparatus according to the present invention, the shield section may have a shield surface extending from the vicinity of the edge of the opening to above the opening.

When the shield section is provided with the shield surface extending from the vicinity of the edge of the opening to above the opening as in this structure, the shield section of the simple structure blocks paths of contaminant particles jumping out of the opening of the internal wall of the guide tube and directly arriving at the substrate in the ion implantation section.

In the ion implantation apparatus according to the present invention, the shield section may have a shield surface intersecting with straight lines running from points on a surface specified by the opening of the introducing section to points on a surface specified by the outlet aperture of the ion beam section.

With provision of this shield surface, the shield surface blocks paths of contaminant particles jumping out though the opening of the introducing section and directly arriving at the substrate, even in the middle of movement of a substrate at the position facing the

outlet aperture.

In the ion implantation apparatus according to the present invention, the shield section may have the shield surface making an acute angle with the internal wall surface of the guide tube and having a flat plate shape. The shield section may be configured to include a flat plate having the shield surface and placed at an acute angle to the internal wall surface of the guide tube, and a frame member for supporting this flat plate.

Brief Description of the Drawings

Fig. 1 is an exploded perspective view to show an ion implantation apparatus according to the present invention.

Fig. 2 is a schematic structural diagram of the ion implantation apparatus according to the present invention.

Fig. 3 is a perspective view of the interior of the beam guide section obtained when the outlet aperture is viewed from the inlet aperture.

Fig. 4 is a longitudinal cross-sectional view as a cross section along I-I' of Fig. 3, which schematically depicts the beam guide section in a plane including an axis directed in the traveling direction of the ion beam.

Fig. 5 is a cross-sectional view as a cross section along II-II' of Fig. 4.

Best Mode for Carrying Out the Invention

A preferred embodiment of the present invention will be described hereinafter with reference to the drawings. The same portions will be denoted by the same reference symbols and redundant description will be omitted, as much as possible.

The ion implantation apparatus 10 according to the embodiment of the present invention will be described referring to Fig. 1 and Fig. 2. Fig. 1 is an exploded perspective view to show the preferred embodiment of the ion implantation apparatus according to the present invention. Fig. 2 is a schematic structural diagram of the ion implantation apparatus of the present embodiment.

Referring to Fig. 1 and Fig. 2, the ion implantation apparatus 10 is mainly comprised of an ion source section 12, an ion implantation section 14, and a beam guide section 24.

The ion source section 12 generates ions to form an ion beam (IB). Wafers (substrates) W are placed in the ion implantation section 14, and the ions generated in the ion source section 12 are implanted in the wafers W. The beam guide section 24 has an inlet aperture for accepting the ions, connected to the ion source section 12 (more precisely, to a postacceleration system 23 described hereinafter), an

outlet aperture as an opening to the ion implantation section 14, for delivering the ions thereinto, and a guide tube extending from the inlet aperture to the outlet aperture.

5 The ion source section 12 has an ion generating system 18, an ion beam extraction preacceleration system 20, a mass analyser system 22, and a postacceleration system 23. Each of these systems is housed in a housing or a tube (pipe). Vacuum pumps as
10 pressure reducing means, e.g., turbo molecular vacuum pumps 26, 28 are connected to the ion beam extraction preacceleration system 20 and to the postacceleration system 23, respectively. For this reason, the interior of each of the ion beam extraction preacceleration
15 system 20 and the postacceleration system 23 is depressurized to a predetermined vacuum.

 The ion generating system 18 is able to produce a high density plasma including doping ions by inducing discharge in a gas containing a doping impurity
20 supplied from a gas supply source (not illustrated). The ion beam extraction preacceleration system 20 extracts the doping ions from the plasma in the ion generating system 18 by making use of a potential difference from the ion generating system 18 and
25 accelerates the doping ions to form the ion beam (IB). A magnet for mass analysis (not illustrated) is

disposed in the mass analyser system 22. Therefore,
only ion species determined by the kinetic energy
acquired in the ion extraction preacceleration system
20 and the magnetic field of the mass analysis magnet
are taken out of the ion source section 12. After
taken out of the ion source section 12, the ion beam
(IB) is further accelerated while passing the
postacceleration system 23. The ion beam acquires
predetermined kinetic energy (acceleration energy)
suitable for the ion implantation before arrival at the
beam guide section 24.

The beam guide section (tube) 24 is connected at
the inlet aperture to the postacceleration system 23.
The beam guide section 24 accepts the ions through this
inlet aperture and delivers the ions through the outlet
aperture opening opposite to the ion implantation
section 14. The ions are injected into the wafer W in
the ion implantation section 14.

On the other hand, the ion implantation section
14 is provided with a target chamber 30 of a box type,
and a wafer support wheel 32 disposed in the target
chamber 30.

The guide section 24 is located on one wall
surface of the target chamber 30 so that an opening 34
of the beam guide section 24 connected at one end
thereof to the postacceleration system 23 can face the

wafer W. The beam guide section 24 projects with the opening 34 being directed into the target chamber 30. A beam stop 36 is located at a position opposite to the opening 34 in another wall surface. The beam stop 36 is a stop for receiving the ion beam (IB) having passed the wafer support wheel 32, and an ion detector for detecting an ion beam irradiation amount is located there for controlling the ion implantation. Vacuum pumps as second pressure reducing means, for example, cryopumps 42, 44 are connected each through a valve 38, 40 on the wall surface of the target chamber 32 to the ion implantation section 14.

The wafer support wheel 32 consists of a swing shaft 46 mounted in a swingable state in the target chamber 30, a hub 48 mounted in a rotatable state to the distal end of the swing shaft 46, and a plurality of arms 50 radially extending from the hub 48. A wafer holder 52 for holding a wafer W is provided at the distal end of each arm 50. The hub 48 is driven to rotate in a direction of an arrow A illustrated in Fig. 1 and the swing shaft 46 is swung in a predetermined angle range along directions of arrows B illustrated in Fig. 1.

A wafer loader section 16 is disposed adjacent to the target chamber 30. In the wafer loader section 16, a transfer path 56 keeps a housing 54 and the target

chamber 30 in communication with each other. This transfer path 56 is provided with an isolation valve 58 to separate the housing 54 from the target chamber 30. This allows only the wafer loader 16 to be opened to the atmosphere, so that an operator can place a cassette (not illustrated) accommodating a plurality of wafers W, in the housing 54. The wafers W in the cassette can be transferred and mounted on the respective wafer holders 52 of the wafer support wheel 32 in the target chamber 30 by a robot (not illustrated).

The beam guide section 24 will be described referring to Fig. 3 to Fig. 5. Fig. 3 is a perspective view of the interior of the beam guide section 24 as a view of outlet aperture 24b from inlet aperture 24a. Fig. 4 is a cross-sectional view as a cross section along I-I' of Fig. 3. Fig. 4 is the cross-sectional view to schematically show the beam guide section 24 in a plane including the axis directed in the traveling direction of the ion beam. Fig. 5 is a cross-sectional view as a cross section along II-II' of Fig. 4.

In the beam guide section 24, the inlet aperture 24a is connected to the postacceleration system (denoted by numeral 23 in Fig. 2) of the ion source section and the outlet aperture 24b has the opening 34 in communication with the interior of the ion

implantation section (denoted by numeral 14 in Fig. 2). The inlet aperture 24a and outlet aperture 24b are connected by a guide tube 24c extending from the inlet aperture 24a to the outlet aperture 24b. Therefore, the interior of the guide tube 24c is a passage for the ion beam 64 to pass, and the ions having passed through the guide tube arrive at the wafer 92. The wafer 92 is mounted on a wafer holder 52. Similarly, wafers 94 are mounted on other wafer holders 52. These wafers rotate at high speed in the plane normal to the direction of the traveling axis of the ion beam 64. Since this arrangement causes these wafers 92, 94 to successively move relative to the ion beam (in the direction of an arrow C in Fig. 4), the ions are repeatedly implanted in these wafers 92, 94.

A charged particle generator 62 is disposed on an outer side surface of the beam guide section 24. This charged particle generator 62 is disposed in the target chamber 30. The charged particle generator 62 includes a filament coil 68 having two terminals, a plasma generating chamber 66 housing the filament coil 68, and a plasma intensifying magnet 70 for intensifying the plasma generated in the plasma generating chamber 66. The two terminals 68a, 68b of the filament coil 68 are drawn out in an electrically insulated state from one surface of the plasma generating chamber 66 to the

outside of the chamber to be connected to a power supply 72. The power supply 72 is, for example, one having the dc voltage of 5 volts and the current supply capacity of 200 amperes.

5 In order to generate the plasma in the plasma generating chamber 66, a filler gas, e.g., argon gas is supplied through a gas supply tube 74 to the plasma generating chamber 66. Since the electric current flowing in the filament coil 68 heats the filament
10 itself, the filament coil 68 emits thermoelectrons into the plasma generating chamber 66. A power supply 78 is connected between the filament coil 68 and a peripheral part 76 of the chamber 66 so that the chamber 66 side has a higher potential than the filament coil 68. The
15 power supply 78 is, for example, one having the dc voltage of 50 volts and the current supply capacity of 6 amperes. When the filament coil 68 comes to emit thermoelectrons, the plasma is generated in the chamber 66 to increase electrons emitted from the filament.
20 Therefore, the charged particle generator 62 is an electron generator and thus has the function of a charge neutralizer.

 An introducing tube (introducing section) 80 connects the plasma generating chamber 66 with the beam
25 guide section 24. The introducing tube 80 has its opening 82 in the internal wall 24d of the guide tube

24c, so that the charged particles from the charged particle generator 62 are guided through this opening 82 into the guide tube 24c. For this reason, part of the thermoelectrons generated pass through the introducing tube 80 because of diffusion thereof to be released into the beam guide section 24. A typical shape of such an opening 82 is a circle or an ellipse and the typical size thereof is 3 mm to 5 mm in the diameter passing the center.

Meanwhile, the filament 68 heated by the electric current also emits particles of a metal material making the electrode, as well as the thermoelectrons. In the charged particle generator 62 of the ion implantation apparatus, the filament 68 is made of tungsten. Therefore, the charged particle generator 62 also emits tungsten atoms together with electrons. If the tungsten atoms were introduced into the silicon wafer, they could cause an unwanted effect on semiconductor devices. Therefore, it is necessary to employ a means for preventing the tungsten atoms from reaching the wafer.

For this purpose, the ion implantation apparatus 10 of the present embodiment is provided with a shield section 84. The shield section 84 is located between the opening 82 of the introducing tube 80 and the outlet aperture 24b on the internal wall surface 24d of

the guide tube 24c.

The following will describe the reason why this shield section 84 is suitable for prevention of contamination of wafers. The charged particle generator 62 for generating the charged particles having the charge opposite to that of the ions is provided in the beam guide section 24 through which the ions generated in the ion source section 18 (see Fig. 2) pass to be introduced into the ion implantation section 14 (see Fig. 2). For this reason, the charged particle generator 62 also generates the contaminant particles (tungsten atoms of the constituent element making the filament) which are contaminants for the wafers. However, when the shield section 84 located between the opening 82 of the introducing tube 80 and the outlet aperture 24b is placed on the internal wall 24d of the guide tube 24a, it blocks paths of particles jumping out through the opening 82 of the internal wall 24d of the guide tube and directly reaching the wafer 92. Therefore, the shield section prevents the tungsten atoms from contaminating the wafers.

In the example illustrated in Fig. 4, the paths to be blocked are only those of the particles jumping out through the opening 82 and directly reaching the wafer 92. Concerning it, the inventor considers the reason as follows. In general, the interior of the

beam guide section 24 of such ion implantation apparatus is maintained in high vacuum. The reason is that the vacuum in which the ions of the ion beam 64 rarely collide with remaining gas, needs to be achieved in order to permit very large part of the ion beam 64 entering through the inlet aperture 24a to reach the outlet aperture 24b. When the beam guide section 24 is maintained in such a vacuum, the probability of the particles colliding with the ion implantation apparatus or the wall surface 24d of the beam guide section 24 or the like is greater than the probability of the particles therein colliding with each other.

Accordingly, though the tungsten atoms jumping out through the opening 82 have velocities in various directions, the tungsten atoms, particularly, with velocity vectors directed toward the wafer 92, specifically, with velocity vectors within dashed lines 88 in the example of Fig. 4 can directly reach the surface of the wafer 92 unless they collide with other particles. The particles with other velocity vectors have to change their directions of motion toward the wafer 92 by colliding with the wall surface 24d. This probability is small. It is thus sufficient to block the paths of the tungsten atoms jumping out through the opening 82 and directly reaching the wafer 92.

Referring to Fig. 4 and Fig. 5, the region

between chain double-dashed lines 86 indicates a situation in which as a result of movement the wafer 92 has arrived at the position where the entire surface thereof appears in the outlet aperture 24b of the beam guide section 24. The region between dashed lines 88 indicates a situation in which after further movement the wafer 92 has arrived at the position where the entire surface thereof appears approximately in the center of the outlet aperture 24b of the beam guide section 24. The region between chain lines 90 indicates a situation in which after further movement the wafer 92 has arrived at the position where part of the surface thereof starts leaving the outlet aperture 24b of the beam guide section 24.

With examples of two typical points 82a, 82b on the periphery of the opening 82, the matter necessary for prevention of contamination of wafers will be further described. The point 82a is the closest point to the outlet aperture 24b out of those on the opening 82 and the point 82b the farthest point from the outlet aperture 24b out of those on the opening 82. A shield surface 84a of the shield section 84 intersects with at least part of a group of straight lines running from the point 82a to points on the surface of the wafer 92. Likewise, the shield surface 84a of the shield portion 84 intersects with at least part of a group of straight

lines from the point 82b to points on the surface of the wafer 92. The tungsten atoms flying in paths indicated by the intersecting lines collide with the shield section 84, i.e., with the shield surface 84a before reaching the wafer surface. Therefore, such atoms do not reach the wafer surface.

The above described the typical points 82a and 82b, but a similar group of straight lines is also defined at each point on the opening surface specified by the opening 82. In order to prevent the contamination caused by the tungsten atoms, it is preferable to provide the shield surface 84a so that the shield surface 84a of the shield section 84 intersects with at least part of such straight line groups consisting of all the straight lines defined at the respective points as described above.

Particularly, in the cross section (plane) illustrated in Fig. 4, the shield surface 84a of the shield section 84 intersects with all the straight lines running from the point 82a to the respective points on the surface of the wafer 92. Similarly, the shield surface 84a of the shield section 84 intersects with all the straight lines running from the point 82b to the respective points on the surface of the wafer 92. The shield surface 84a also intersects with all the straight lines running from each of the points on the

surface specified by the opening 82 to each of the points on the surface of the wafer 92.

Fig. 5 depicts a case in which the shield surface 84a intersects with all the straight lines running from all the points on the surface of the opening 82 to each point on the surface of the wafer 92, and an outline 84b defined by the group of these straight lines is illustrated on the shield surface 84a of the shield section 84. In this case, the contamination can be prevented almost perfectly.

The shield surface 84a will be described below in more detail.

The shield surface 84a is preferably a surface intersecting with the straight lines running from each of the points on the surface specified by the opening 82 of the introducing tube 80 to each of the points on the surface to be implanted in the wafer 92 placed in the ion implantation section 14. When such a shield surface 84a is placed, it blocks the paths of the contaminant particles jumping out through the opening 82 of the internal wall 24d of the guide tube and directly reaching the wafer 92.

The shield surface 84a is preferably shaped so as to extend from the vicinity of the edge 82a of the opening 82 to above the opening 82. By providing the shield surface 82a of this shape, the shield section 84

of the simple structure blocks the paths of the contaminant particles jumping out through the opening of the internal wall 24d of the guide tube and directly reaching the wafer in the ion implantation section 14.

5 Further, the shield surface 84a is preferably one intersecting with straight lines running from each of the points on the surface specified by the opening 82 of the introducing tube 80 to each of points on the surface specified by the outlet aperture 24b of the ion beam section 24. By providing the shield surface 84a of this type, the shield section blocks the paths of the contaminant particles jumping out through the opening 82 of the internal wall 24d of the guide tube and directly reaching the wafer 92 everywhere the wafer 92 moves across the outlet aperture.

10 The shield section 84 of this type can be a flat-plate-shape member which has the shield surface 84a at one end, the shield surface 84a making an acute angle with the wall surface 24d of the guide tube, and which extends in the direction of the ion beam 64 on the internal wall 24d. The shield section 84 may also be constructed of a flat plate one surface of which forms the shield surface 84a and which extends at an acute angle from the wall surface 24d, and a frame member supporting the flat plate.

25 Referring to Fig. 3, the illustration includes

only the beam guide section 24, the charge generating section 62, and the shield section 84 for simplicity. The opening 82 of the introducing tube 80 is located in the internal wall 24d of the beam guide section 24.

5 The outline 84b of the group of straight lines connecting between the points on the opening 80 and the points on the wafer 92 is illustrated on the shield surface 84a of the shield section 84. Since the shield plane 84a is arranged to extend so as to cover the
10 region from the edge of the opening 82 to above the opening 82 in this way, it can intersect with at least part of such a group of straight lines. The shield plane 84a is preferably formed so as to intersect with all the group of straight lines.

15 A material suitable for formation of such a shield section 84 is preferably graphite. As another example, the shield portion 84 is made of a predetermined material and thereafter it is coated with graphite by a surface coating treatment, thereby
20 preventing the contamination.

The results of experiments will be presented below as to the ion implantation apparatus provided with the shield section 84 for shielding the filament 68 as described above. The ion implantation conditions
25 employed for the experiments were as follows.

Ion species: As

Acceleration energy: 80 keV

Dose: $5 \times 10^{15}/\text{cm}^2$

Analysis was conducted to measure amounts of tungsten in substrates with or without the shield section 84 under the above conditions. This analysis was carried out by inductively coupled plasma mass spectrometry (ICP-MS). The experiment results were as follows:

before attachment of the filament shield: 2.4×10^{12} atoms/cm²;

after attachment of the filament shield: 1.6×10^{10} atoms/cm².

The shield section 84 was provided so as to block the entire viewing angle range from the wafer to the opening in communication with the chamber housing the filament. As a result, the number of atoms of the contaminant element was reduced to below one tenth.

Industrial Applicability

As detailed above, the ion implantation apparatus according to the present invention is constructed so that the charged particle generator is attached to the beam guide section through which the ion beam passes to be delivered to the ion implantation section. For this reason, the charged particle generator also generates the contaminant particles of contaminating matter for the substrate together with the charged particles

having the charge opposite to that of the ions.

However, since the shield section located between the opening of the introducing section and the outlet aperture is provided on the internal surface of the

5 guide tube, it can block the paths of the contaminant particles jumping out through the opening of the internal wall of the guide tube and reaching the substrate. Therefore, the invention provides the ion implantation apparatus capable of preventing the
10 substrate from being contaminated by the contaminant particles generated by the charged particle generator.

CLAIMS

1. An ion implantation apparatus comprising:
an ion source section for generating ions;
an ion implantation section for implanting said
5 ions generated in said ion source section, in a
substrate;

a charged particle generator for generating
charged particles having a charge opposite to that of
said ions;

10 a beam guide section having an inlet aperture for
accepting said ions from said ion source section, an
outlet aperture for delivering said ions into said ion
implantation section, a guide tube extending from said
inlet aperture to said outlet aperture, and an
15 introducing section having an opening thereof in an
internal surface of said guide tube, for introducing
said charged particles from said charged particle
generator into said guide tube; and

20 a shield section located between said opening of
said introducing section and said outlet aperture
inside said guide tube.

25 2. The ion implantation apparatus according to
Claim 1, wherein said shield section comprises a shield
surface intersecting with straight lines running from
points on a surface specified by said opening of said
introducing section to points on a surface of said

substrate to be implanted with the ions, placed in said ion implantation section.

3. The ion implantation apparatus according to Claim 1, wherein said shield section comprises a shield surface extending from the vicinity of the edge of said opening to above said opening.

4. The ion implantation apparatus according to Claim 1, wherein said shield section comprises a shield surface intersecting with straight lines running from points on a surface specified by said opening of said introducing section to points on a surface specified by said outlet aperture of said ion beam section.

5. The ion implantation apparatus according to Claim 2, wherein said shield section comprises said shield surface making an acute angle with the internal wall surface of said guide tube and having a flat plate shape.

6. The ion implantation apparatus according to Claim 2, wherein said shield section comprises a flat plate having said shield surface and placed at an acute angle to the internal wall surface of said guide tube, and a frame member for supporting said flat plate.

ABSTRACT

An ion implantation apparatus comprises an ion source section (18) for generating ions; an ion implantation section (14) for implanting the ions generated in the ion source section (18), in a substrate (92); a charged particle generator (62) for generating charged particles having a charge opposite to that of the ions; a beam guide section (24) having an inlet aperture (24a) for accepting the ions from the ion source section (18), an outlet aperture (24b) for delivering the ions into the ion implantation section (18), a guide tube (24c) extending from the inlet aperture (24a) to the outlet aperture (24b), and an introducing section (80) having an opening (82) thereof in an internal surface (24d) of the guide tube (24c), for introducing the charged particles from the charged particle generator (62) into the guide tube (24c); and a shield section (84) located between the opening (82) of the introducing section (80) and the outlet aperture (24b) inside the guide tube (24c). A shield surface (84a) of the shield section (84) blocks the charged particles' reaching the wafer.




Fig. 1

Fig.2




Fig.3




Fig. 4





Fig.5

Combined Declaration and Power of Attorney

As a below named inventor, I hereby declare that:

This declaration is of the following type:

☒ original ☐ supplemental

☒ national stage of PCT

☐ divisional ☐ continuation ☐ continuation-in-part

My residence, post office address and citizenship are as stated next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

ION IMPLANTATION APPARATUS

the specification of which

☐ is attached hereto.

☐ was filed on _____
as United States Application Serial Number _____ and,
was amended on _____ (if applicable).

☒ was filed on October 29, 1999
as PCT International Application Number PCT/JP99/06038 and,
was amended under PCT Article 19 on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

PRIOR FOREIGN APPLICATIONS, BENEFIT CLAIMED UNDER 35 USC §119(a)

Application Number	Country	Date of Filing (Day/Month/Year)	Priority Claimed Under 35 USC 119
<u>P1998-310658</u>	<u>Japan</u>	<u>30 / October / 1998</u>	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No

AMJ240/002861
TMY 92

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

PRIOR U.S. PROVISIONAL APPLICATIONS, BENEFIT CLAIMED UNDER 35 USC §119(e)

<u>(Application No.)</u>	<u>(Filing Date)</u>	<u>(Application No.)</u>	<u>(Filing Date)</u>
<u>(Application No.)</u>	<u>(Filing Date)</u>	<u>(Application No.)</u>	<u>(Filing Date)</u>

I hereby claim the benefit of Title 35, United States Code Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS
DESIGNATING THE U.S., BENEFIT CLAIMED UNDER 35 USC §120

<u>PCT/JP99/06038</u>	<u>October 29, 1999</u>	<u>Pending</u>
<u>(Application No.)</u>	<u>(Filing Date)</u>	<u>(Status: Patented, Pending, Abandoned)</u>
<u>(Application No.)</u>	<u>(Filing Date)</u>	<u>(Status: Patented, Pending, Abandoned)</u>

POWER OF ATTORNEY: As a named inventor, I hereby appoint the registered practitioners of MCDERMOTT, WILL & EMERY included in the Customer Number provided below to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Customer Number 20277

Send Correspondence to: Customer Number 20277

MCDERMOTT, WILL & EMERY

600 13TH STREET, N.W.
WASHINGTON, D.C., 20005-3096

Direct Telephone Calls to: 202-756-8000

AMJ240/00286
TMN 11-31

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Full Name of sole or first inventor Hiroiyuki ITO	
Inventor's signature <i>Hiroiyuki Ito</i>	Date April 24, 2001
Residence Narita-shi, Chiba, Japan JPK	
Citizenship Japan	
Post office address c/o Applied Materials Japan, Inc., 14-3, Shinizumi, Narita-shi, Chiba 286-8516 Japan	

Full Name second joint inventor, if any Hiroshi ASECHI	
Second inventor's signature <i>阿世知 大</i>	Date April 24, 2001
Residence Narita-shi, Chiba, Japan JPK	
Citizenship Japan	
Post office address c/o Applied Materials Japan, Inc., 14-3, Shinizumi, Narita-shi, Chiba 286-8516 Japan	

PTO/ACT Rec'd 30 APR 2001

Docket No.: 50212-225

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of :
Hiroyuki ITO, et al. :
Serial No.: : Group Art Unit:
Filed: April 30, 2001 : Examiner:
For: ION IMPLANTATION APPARATUS

ASSOCIATE POWER OF ATTORNEY

Honorable Commissioner for Patents and Trademarks
Washington, D. C. 20231

Sir:


The undersigned Principal Attorney of record hereby appoints the following Attorneys as his Associates with regard to the above-identified application: Stephen A. Becker, Reg. No. 26,527; John G. Bisbikis, Reg. No. 37,095; Christopher D. Bright, Reg. No. 46,578; Daniel Bucca, Reg. No. 42,368; Kenneth L. Cage, Reg. No. 26,151; Jennifer Chen, Reg. No. 42,404; Bernard P. Codd, Reg. No. 46,429; Lawrence T. Cullen, Reg. No. 44,489; Paul Devinsky, Reg. No. 28,553; Margaret M. Duncan, Reg. No. 30,879; Shamita De. Etienne-Cummings, Reg. No. 46,072; Ramyar M. Farid, Reg. No. 46,692; Brian E. Ferguson, Reg. No. 36,801; Michael E. Fogarty, Reg. No. 36,139; John R. Fuisz, Reg. No. 37,327; Willem F. Gadiano, Reg. No. 37,136; Keith E. George, Reg. No. 34,111; Matthew V. Grumbling, Reg. No. 44,427; John A. Hankins, Reg. No. 32,029; Joseph Hyosuk Kim, Reg. No. 41,425; Eric J. Kraus, Reg. No. 36,190; Catherine Krupka, Reg. No. 46,227; Jack Q. Lever, Reg. No. 28,149; Raphael V. Lupo, Reg. No. 28,363; Michael A. Messina, Reg. No. 33,424; Dawn L. Palmer, Reg. No. 41,238; Joseph H. Paquin, Jr., Reg. No. 31,647; Scott D. Paul, Reg. No. 42,984; William D. Pegg, Reg. No. 42,988; Robert L. Price, Reg. No. 22,685; Gene Z. Robinson, Reg. No. 33,351; Joy Ann G. Serauskas, Reg. No. 27,952; Daniel H. Sherr, Reg. No. 46,425; David A. Spenard, Reg. No. 37,449; Arthur J. Steiner, Reg. No. 26,106; David L. Stewart, Reg. No. 37,578; Wesley Strickland, Reg. No. 44,363; Michael D. Switzer, Reg. No. 39,552; Daniel S. Trainor, Reg. No. 43,959; Cameron K. Weiffenbach, Reg. No. 44,488; Aaron Weisstuch, Reg. No. 41,557; Edward J. Wise, Reg. No. 34,523; Jeffrey A. Woller, Reg. No. 48,041; Alexander V. Yampolsky, Reg. No. 36,324; and Robert W. Zelnick, Reg. No. 36,976 all of

Serial No.:

McDERMOTT, WILL & EMERY
600 13th Street, N.W.
Washington, DC 20005-3096

Please continue to address all communications to the undersigned.

April 30, 2001

By 

Arthur J. Steiner
Registration No. 26,106
Attorney for Applicant